

SCALING HAMMERS

These tools have proven to be very efficient in cleaning heavily oxidized surfaces which occur on ships' hulls, bridges and storage tanks.



FS-2A



FS-2A-1F

GLOBAL SPECIFICATIONS

Model	Blows	Piston Diameter		Stroke		Angle Height		Overall Length		Weight		Air Consumption (at Load)		Air Hose Size	
	Hz	mm	in	mm	in	mm	in	mm	in	kg	lb	m ³ /min	ft ³ /min	mm	in
FS-2A	133	30	1.18	16	0.63	94	3 11/16	510	20.1	2.5	5.5	0.25	8.8	9.5	3/8
FS-2A-1F	133	30	1.18	16	0.63	94	3 11/16	537	21.1	2.5	5.5	0.25	8.8	9.5	3/8

Air Inlet Thread Size: PT 3/8"

TOOL SELECTION GUIDE

Standard models

Model	Throttle	
	Lever	Locking Lever (F)
FS-2A	541 205 3480	
FS-2A-1F		541 205 3482

CE certified models

Model	Throttle	
	Lever	Locking Lever (F)
FS-2A-1F EC	541 207 2318	

For CE region availability of non CE models, please inquire to your Fuji representative.

SAND RAMMERS

Fuji sand rammers are powerful but light with a stroke range from 50mm to 127mm. Fuji sand rammers are excellent for ramming sand for casting in any ferrous or non-ferrous foundry. Non-rotary type rammers are available for use with irregular shaped butts.



FR-18B~25B



FR-18L~32



FR-18B-2F~25B-2F



FR-18L-2F~32-2F

GLOBAL SPECIFICATIONS

Model	Blows	Piston Diameter		Stroke		Angle Height		Overall Length		Weight		Air Consumption (at Load)		Air Hose Size	
	Hz	mm	in	mm	in	mm	in	mm	in	kg	lb	m ³ /min	ft ³ /min	mm	in
FR-18B	30	18	0.709	50	1.97	41	1 5/8	280	11	1.5	3.3	0.40	14.1	9.5	3/8
FR-18L	30	18	0.709	50	1.97	41	1 5/8	558	22	2	4.4	0.40	14.1	9.5	3/8
FR-22B	17	22	0.866	64	2.52	51	2 1/32	350	13.8	3	6.6	0.50	17.7	9.5	3/8
FR-22L	17	22	0.866	64	2.52	51	2 1/32	633	24.9	3.3	7.2	0.50	17.7	9.5	3/8
FR-25B	13	25.4	1	83	3.27	67	2 3/5	506	19.21	5.5	12.1	0.70	24.7	12.7	1/2
FR-25L	13	25.4	1	83	3.27	67	2 3/5	597	22.3	5.5	12.1	0.70	24.7	12.7	1/2
FR-32	12	32	1.26	127	5	75	3	1086	42.8	10	22.1	0.80	28.2	12.7	1/2

TOOL SELECTION GUIDE

Standard models

Model	Throttle	
	Lever	Locking Lever (2F)
FR-18B E	541 205 3216	541 205 3218
FR-18L E	541 205 3221	541 205 3223
FR-22B	541 205 3225	541 205 3227
FR-22L	541 205 3229	541 205 3231
FR-25B	541 205 3233	541 205 3235
FR-32	541 205 3241	541 205 3243

CE certified models

Model	Throttle
	Locking Lever (2F)
FR-18B-2F	541 207 2109
FR-18L-2F	541 207 2112
FR-22B-2F	541 207 2115
FR-22L-2F	541 207 2116
FR-25B-2F	541 207 2118
FR-25L-2F	541 207 2119
FR-32-2F	541 207 2121

For CE region availability of non CE models, please inquire to your Fuji representative.

NPT models

Model	Throttle	
	Lever	Locking Lever (2F)
FR-18B	541 205 3215	541 205 3217
FR-18B-2F		
FR-18L-2F		541 205 3224
FR-22B	541 205 3226	
FR-25B	541 205 3234	
FR-25L	541 205 3238	
FR-32	541 205 3242	

For possibility of NPT inlet for other models, please inquire to your Fuji representative.